

SN - 15

Optical Compressor

OPERATION

- 1 - Connect the input jack to your instrument
- 2 - Connect the output jack to your pedal chain or directly to amplifier

CONTROLS:

RATIO: Ratio from 2:1 to 6:1

THRESHOLD: Threshold (- 18dBu / + 10dBu)

ATTACK: Attack from 1ms to 100ms

VOL PRE: Master volume

Rear Panel Connections:

INPUT: Jack(Mono)

OUTPUT: Jack(Mono)

DC Adaptor (center negative)



Specifications:

Power Supply: 9v DC

Current Flow: 20mA

Switch: Buffer bypass

Enclosure: Stainless steel 304

Weight: 750gr

Wood Sides: Okoumè black

Size: 110x110x42mm

- Compressor with THR down can be used as a preamp.
- Led-Meter displays the threshold level and the attack speed too. Compressor can accept input signal up to 2V RMS



IMPORTANT: Use only power supplies for musical instruments (e.g. One Spot or superior). FKT Audio decline any responsibility for the use of unstabilized or unsuitable power supplies.



FKT AUDIO®

Warranty

FKT Audio warrants the product to be free from defects in material and workmanship for a period of 3 years from the original date of purchase. if the product fails within the warranty period, FKT Audio will repair or, at our discretion, replace the product at no cost to the original purchaser.

Exclusions

This warranty covers defects in manufacturing discovered while using this product as recommended by FKT Audio.

This warranty does not cover loss or theft, nor does the coverage extend to damage caused by misuse, abuse, unauthorized modification, improper storage, lightning, or natural disasters.

Limits of Liability

In the case of malfunction, the product will be repaired or replaced, as described above. FKT Audio will not be liable to any party for damages arising from the failure of this product.

The following damages are not included: damage to other equipment and damages incidental to or arising from the inability to use this product.

